



GreenUp Grid

GD309B 3*P20 940 PSU-E VWB

GreenUp Grid, 54 W, 66 W, 940 neutral white, IP20 | Finger-protected

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenSpace Grid product family offers a complete range of options with comprehensive control availability, optical solutions and powerful lumen outputs, meanwhile ensures the product reliability and quality within compact luminaire body.

Product data

General Information	
Light source engine type	LED
Light Technical	
Luminous Flux	4,800 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color rendering index (CRI)	>90
Light source color	940 neutral white
Operating and Electrical	
Input Voltage	200 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	54 66 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	-

Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Aluminum Alloy
Optical cover material	Acrylate
Housing Color	White
Optical cover finish	Frosted
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Optical cover type	Acrylate
Net Weight (Piece)	2.030 kg

GreenUp Grid

Approval and Application

CE mark	No
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	GD309B 3*P20 940 PSU-E VWB
--------------------	----------------------------

Full product name	GD309B 3*P20 940 PSU-E VWB
Full product code	872016952430999
Order code	911401512312
Material Nr. (12NC)	911401512312
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169524309
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169535794

Dimensional drawing

