



GreenUp Grid

GD309B 3*P33 930 PSU-E MB

GreenUp Grid, 108.9 W, 89.1 W, 930 warm white, IP20 | Finger-protected

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenSpace Grid product family offers a complete range of options with comprehensive control availability, optical solutions and powerful lumen outputs, meanwhile ensures the product reliability and quality within compact luminaire body.

Product data

General Information		Protection class IEC	
Light source engine type	LED		Safety class II
Light Technical		Controls and Dimming	
Luminous Flux	8,510 lm	Dimmable	No
Correlated Color Temperature (Nom)	3000 K	Control interface	-
Luminous Efficacy (rated) (Nom)	86 lm/W	Mechanical and Housing	
Color rendering index (CRI)	>90	Housing Material	Aluminum Alloy
Light source color	930 warm white	Optical cover material	Acrylate
Operating and Electrical		Housing Color	White
Input Voltage	200 to 240 V	Optical cover finish	Frosted
Line Frequency	50 to 60 Hz	Ingress protection code	IP20 [Finger-protected]
Power Consumption	108.9 89.1 W	Mech. impact protection code	IK03 [0.3 J]
Power Factor (Fraction)	0.9	Optical cover type	Acrylate
Number of products on MCB of 16 A type B	-	Net Weight (Piece)	2.030 kg

GreenUp Grid

Approval and Application

CE mark	No
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	GD309B 3*P33 930 PSU-E MB
--------------------	---------------------------

Full product name	GD309B 3*P33 930 PSU-E MB
Full product code	872016952936699
Order code	911401559312
Material Nr. (12NC)	911401559312
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169529366
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169540859

Dimensional drawing

