



Flex Cove - Neon Indoor

LS360S LED3 P10 3000K L5 0612 S

Flex Cove - Neon Indoor, 315 lm, 31.5 lm/W, 930 warm white, Opal, 24 V, IP44 | Wire-protected, splash-proof

Philips FlexCove Neon Indoor is a NEW offer in addition to our popular LED cove lighting. This comprehensive new family of flexible strip lights are designed to follow straight lines or curves to create beautiful ambiances that highlight architectural details in mono white, tunable white or colored light. These customizable cove lighting strips also promise superb lighting uniformity within small light mixing distances and limited installation spaces, color consistency and easy installation. All with a long lifetime that promises less lumen decay or color shifts. So with FlexCove Neon Indoor, you can flex your accent lighting to suit the requirements of any project - beautifully.

Product data

General Information		Operating and Electrical	
Light source engine type	LED	Input Voltage	24 V
Light Technical		Line Frequency	- Hz
Luminous Flux	315 lm	Power Consumption	44 W
Correlated Color Temperature (Nom)	3000 K	Power Factor (Fraction)	-
Luminous Efficacy (rated) (Nom)	31.5 lm/W	Number of products on MCB of 16 A type B	-
Color rendering index (CRI)	90	Protection class IEC	Safety class III
Light source color	930 warm white	Controls and Dimming	
Unified glare rating CEN	Not applicable	Dimmable	Yes - Check ballast compatibility
		Control interface	depends on driver (1-10V, DALI...)

Flex Cove - Neon Indoor

Mechanical and Housing	
Housing Material	Silicon
Optical cover material	Silicon tube
Housing Color	White
Optical cover finish	Opal
Overall length	5,000 mm
Overall width	6 mm
Overall height	12 mm
Dimensions (Height x Width x Depth)	12 x 6 x 5000 mm
Ingress protection code	IP44 [Wire-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]
Optical cover type	Without lens
Net Weight (Piece)	0.355 kg
Approval and Application	
Flammability mark	-
CE mark	No

Performance ambient temperature Tq	25 °C
Ambient temperature range	-20 to +45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	LS360S LED3 P10 3000K L5 0612 S
Full product name	LS360S LED3 P10 3000K L5 0612 S
Order code	911401516144
Material Nr. (12NC)	911401516144
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Dimensional drawing

