



# GreenUp Linear Flex

## RS309B P30/830 L120W5 PSU-E HD 2 BK

GreenUp Linear Flex, 65 lm/W, 830 warm white

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Linear Flex is a comprehensive product family which offers a variety of combinations between decorative and functional lighting units. It supports every of your desires with flexible linear family including suspension and recessed installations.

### Product data

General Information		Control interface	
Light source engine type	LED		-
Light Technical		Mechanical and Housing	
Luminous Flux	1,950 lm	Housing Material	Aluminum extruded
Correlated Color Temperature (Nom)	3000 K	Optical cover material	Polycarbonate
Luminous Efficacy (rated) (Nom)	65 lm/W	Housing Color	Black
Color rendering index (CRI)	>80	Optical cover finish	Frosted
Light source color	830 warm white	Ingress protection code	IP20 [Finger-protected]
Operating and Electrical		Mech. impact protection code	IK03 [0.3 J]
Input Voltage	220-240 V	Optical cover type	Linear-lens array oval shape
Line Frequency	50 or 60 Hz	Net Weight (Piece)	1.270 kg
Power Consumption	30 W	Approval and Application	
Power Factor (Fraction)	0.9	CE mark	No
Number of products on MCB of 16 A type B	70	Ambient temperature range	-20 to +40 °C
Protection class IEC	Safety class II	Initial Performance (IEC Compliant)	
Controls and Dimming		Luminous flux tolerance	+/-10%
Dimmable	No	Power consumption tolerance	+/-10%

# GreenUp Linear Flex

## Product Data

Order product name	RS309B P30/830 L120W5 PSU-E HD 2 BK
Full product name	RS309B P30/830 L120W5 PSU-E HD 2 BK
Full product code	872016953169799
Order code	911401589722
Material Nr. (12NC)	911401589722

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169531697
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169543188

## Dimensional drawing

