



GreenUp Linear Flex

RS309B P30/840 L120W5 PSU-E HD 2 BK

GreenUp Linear Flex, 70 lm/W, 840 neutral white

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Linear Flex is a comprehensive product family which offers a variety of combinations between decorative and functional lighting units. It supports every of your desires with flexible linear family including suspension and recessed installations.

Product data

General Information	
Light source engine type	LED
Light Technical	
Luminous Flux	2,100 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	70 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	30 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	70
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No

Control interface	-
Mechanical and Housing	
Housing Material	Aluminum extruded
Optical cover material	Polycarbonate
Housing Color	Black
Optical cover finish	Frosted
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Optical cover type	Linear-lens array oval shape
Net Weight (Piece)	1.270 kg
Approval and Application	
CE mark	No
Ambient temperature range	-20 to +40 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

GreenUp Linear Flex

Product Data

Order product name	RS309B P30/840 L120W5 PSU-E HD 2 BK
Full product name	RS309B P30/840 L120W5 PSU-E HD 2 BK
Full product code	872016953042399
Order code	911401589822
Material Nr. (12NC)	911401589822

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169530423
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169541917

Dimensional drawing

