



# GreenSpace Flex

## RS378B P11 927 PSD-E MB M55

GreenSpace Flex, 11 W, 927 warm white, DALI, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information	
Light source engine type	LED
Light Technical	
Luminous Flux	660 lm
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	110 lm/W
Color rendering index (CRI)	>90
Light source color	927 warm white
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	11 W
Power Factor (Fraction)	0.83
Number of products on MCB of 16 A type B	-
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	DALI

Control interface	DALI
Mechanical and Housing	
Housing Material	Aluminum Alloy
Optical cover material	Polymethyl methacrylate
Housing Color	Grey
Optical cover finish	Opal
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Optical cover type	PMMA
Net Weight (Piece)	0.250 kg
Approval and Application	
CE mark	Yes
Ambient temperature range	-20 to +45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

## Greenspace Flex

### Product Data

Order product name	RS378B P11 927 PSD-E MB M55
Full product name	RS378B P11 927 PSD-E MB M55
Full product code	692382865337899
Order code	911401535971
Material Nr. (12NC)	911401535971

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828653378
Numerator - Packs per outer box	36
EAN/UPC - Case	6923828653378

### Dimensional drawing

