



Greenspace Flex

RS378B P11 927 PSU-E NB M55

Greenspace Flex, 11 W, 927 warm white, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General Information		
Number of gear units	1 unit	
Driver included	Yes	
Light source engine type	LED	
Warranty period	3 years	
Light Technical		
Luminous Flux	836 lm	
Correlated Color Temperature (Nom)	2700 K	
Luminous Efficacy (rated) (Nom)	76 lm/W	
Color rendering index (CRI)	>90	
Light source color	927 warm white	
Operating and Electrical		
Input Voltage	220-240 V	
Line Frequency	50 or 60 Hz	
Average CLO power consumption	525 W	
Power Consumption	11 W	
Power Factor (Fraction)	0.9	
Connection	External connector	
Cable	-	

Number of products on MCB of 16 A type B	-
Suitable for random switching	No
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Electronic transformer
Control interface	-
Constant light output	No
Maximum dim level	Not applicable
Mechanical and Housing	
Housing Material	Aluminum Alloy
Optic material	Polymethyl methacrylate
Optical cover material	Polymethyl methacrylate
Fixation material	Aluminum
Housing Color	Grey
Optical cover finish	Opal
Overall height	49 mm
Overall diameter	55 mm
Ingress protection code	IP20 [Finger-protected]

Datasheet, 2025, February 2 data subject to change

Greenspace Flex

Mech. impact protection code	IKO4 [0.5 J standard plus]	
Optical cover type	PMMA	
Net Weight (Piece)	0.190 kg	
A		
Approval and Application		
Glow-wire test	Temperature 600 °C, duration 30 s	
CE mark	Yes	
EU RoHS compliant	Yes	
Ambient temperature range	-20 to +45 °C	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	-10% / +10%	
Initial chromaticity	SDCM<3	
Power consumption tolerance	+/-10%	

Over Time Performance (IEC Compliant)			
Median useful life L80B50	50,000 hour(s)		
Product Data			
Order product name	RS378B P11 927 PSU-E NB M55		
Full product name	RS378B P11 927 PSU-E NB M55		
Full product code	692382864996899		
Order code	911401720982		
Material Nr. (12NC)	911401720982		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	6923828649968		
Numerator - Packs per outer box	48		
EAN/UPC - Case	6923828652371		

Dimensional drawing









Modular Type	D, mm	H, mm
RS378B P6/P11 M55	55	49
RS378B P15 M55	55	49
RS378B P24 M70	70	90
RS378B P33 M87	87	107
RS378B P42 M102	102	116



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.