



# Greenspace Flex

## RS378B P11 930 PSU-E NB M55

Greenspace Flex, 11 W, 930 warm white, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information		Number of products on MCB of 16 A type B	
Number of gear units	1 unit	Suitable for random switching	No
Driver included	Yes	Protection class IEC	Safety class II
Light source engine type	LED	<b>Controls and Dimming</b>	
Warranty period	3 years	Dimmable	No
<b>Light Technical</b>		Driver/power unit/transformer	Electronic transformer
Luminous Flux	510 lm	Control interface	-
Correlated Color Temperature (Nom)	3000 K	Constant light output	No
Luminous Efficacy (rated) (Nom)	85 lm/W	Maximum dim level	Not applicable
Color rendering index (CRI)	>90	<b>Mechanical and Housing</b>	
Light source color	930 warm white	Housing Material	Aluminum Alloy
<b>Operating and Electrical</b>		Optic material	Polymethyl methacrylate
Input Voltage	220-240 V	Optical cover material	Polymethyl methacrylate
Line Frequency	50 or 60 Hz	Fixation material	Aluminum
Average CLO power consumption	570 W	Housing Color	Grey
Power Consumption	11 W	Optical cover finish	Opal
Power Factor (Fraction)	0.9	Overall height	49 mm
Connection	External connector	Overall diameter	55 mm
Cable	-	Ingress protection code	IP20 [Finger-protected]

# Greenspace Flex

Mech. impact protection code	IK04 [0.5 J standard plus]
Optical cover type	PMMA
Net Weight (Piece)	0.190 kg

## Approval and Application

Glow-wire test	Temperature 600 °C, duration 30 s
CE mark	Yes
EU RoHS compliant	Yes
Ambient temperature range	-20 to +45 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Initial chromaticity	SDCM<3
Power consumption tolerance	+/-10%



## Over Time Performance (IEC Compliant)

Median useful life L80B50	50.000 hour(s)
---------------------------	----------------

## Product Data

Order product name	RS378B P11 930 PSU-E NB M55
Full product name	RS378B P11 930 PSU-E NB M55
Full product code	692382864999999
Order code	911401720992
Material Nr. (12NC)	911401720992
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828649999
Numerator - Packs per outer box	48
EAN/UPC - Case	6923828652401

## Dimensional drawing



Modular Type	D, mm	H, mm
RS378B P6/P11 M55	55	49
RS378B P15 M55	55	49
RS378B P24 M70	70	90
RS378B P33 M87	87	107
RS378B P42 M102	102	116

