



# Greenspace Flex

## RS378B P15 930 PSU-E WB M55

Greenspace Flex, 15 W, 930 warm white, 40°, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

| General Information      |         |
|--------------------------|---------|
| Number of gear units     | 1 unit  |
| Driver included          | Yes     |
| Light source engine type | LED     |
| Warranty period          | 3 years |

| Light Technical                    |                |
|------------------------------------|----------------|
| Luminous Flux                      | 580 lm         |
| Correlated Color Temperature (Nom) | 3000 K         |
| Luminous Efficacy (rated) (Nom)    | 97 lm/W        |
| Color rendering index (CRI)        | >90            |
| Light source color                 | 930 warm white |
| Luminaire light beam spread        | 40°            |

| Operating and Electrical      |             |
|-------------------------------|-------------|
| Input Voltage                 | 220-240 V   |
| Line Frequency                | 50 or 60 Hz |
| Average CLO power consumption | 1050 W      |
| Power Consumption             | 15 W        |
| Power Factor (Fraction)       | 0.9         |

|  |                    |
|--|--------------------|
| Connection                               | External connector |
| Cable                                    | -                  |
| Number of products on MCB of 16 A type B | -                  |
| Suitable for random switching            | No                 |
| Protection class IEC                     | Safety class II    |

| Controls and Dimming          |                        |
|-------------------------------|------------------------|
| Dimmable                      | No                     |
| Driver/power unit/transformer | Electronic transformer |
| Control interface             | -                      |
| Constant light output         | No                     |
| Maximum dim level             | Not applicable         |

| Mechanical and Housing |                         |
|------------------------|-------------------------|
| Housing Material       | Aluminum Alloy          |
| Optic material         | Polymethyl methacrylate |
| Optical cover material | Polymethyl methacrylate |
| Fixation material      | Aluminum                |
| Housing Color          | Grey                    |
| Optical cover finish   | Opal                    |

# Greenspace Flex

|                              |                            |
|------------------------------|----------------------------|
| Overall height               | 72 mm                      |
| Overall diameter             | 55 mm                      |
| Ingress protection code      | IP20 [Finger-protected]    |
| Mech. impact protection code | IK04 [0.5 J standard plus] |
| Optical cover type           | PMMA                       |
| Net Weight (Piece)           | 0.260 kg                   |

## Approval and Application

|                           |                                   |
|---------------------------|-----------------------------------|
| Glow-wire test            | Temperature 600 °C, duration 30 s |
| CE mark                   | Yes                               |
| EU RoHS compliant         | Yes                               |
| Ambient temperature range | -20 to +45 °C                     |

## Initial Performance (IEC Compliant)

|                             |             |
|-----------------------------|-------------|
| Luminous flux tolerance     | -10% / +10% |
| Initial chromaticity        | SDCM<3      |
| Power consumption tolerance | +/-10%      |



## Over Time Performance (IEC Compliant)

|                           |                |
|---------------------------|----------------|
| Median useful life L80B50 | 50.000 hour(s) |
|---------------------------|----------------|

## Product Data

|                                 |                             |
|---------------------------------|-----------------------------|
| Order product name              | RS378B P15 930 PSU-E WB M55 |
| Full product name               | RS378B P15 930 PSU-E WB M55 |
| Full product code               | 692382865010099             |
| Order code                      | 911401721322                |
| Material Nr. (12NC)             | 911401721322                |
| Numerator - Quantity Per Pack   | 1                           |
| EAN/UPC - Product/Case          | 6923828650100               |
| Numerator - Packs per outer box | 48                          |
| EAN/UPC - Case                  | 6923828652517               |

## Dimensional drawing



| Modular Type      | D, mm | H, mm |
|-------------------|-------|-------|
| RS378B P6/P11 M55 | 55    | 49    |
| RS378B P15 M55    | 55    | 49    |
| RS378B P24 M70    | 70    | 90    |
| RS378B P33 M87    | 87    | 107   |
| RS378B P42 M102   | 102   | 116   |

