



# Greenspace Flex

## RS378B P15 940 PSD-E WB M55

Greenspace Flex, 15 W, 940 neutral white, DALI, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

| General Information                      |                   |
|--|-------------------|
| Light source engine type                 | LED               |
| Light Technical                          |                   |
| Luminous Flux                            | 1,410 lm          |
| Correlated Color Temperature (Nom)       | 4000 K            |
| Luminous Efficacy (rated) (Nom)          | 94 lm/W           |
| Color rendering index (CRI)              | >90               |
| Light source color                       | 940 neutral white |
| Operating and Electrical                 |                   |
| Input Voltage                            | 220-240 V         |
| Line Frequency                           | 50 or 60 Hz       |
| Power Consumption                        | 15 W              |
| Power Factor (Fraction)                  | 0.9               |
| Number of products on MCB of 16 A type B | -                 |
| Protection class IEC                     | Safety class II   |
| Controls and Dimming                     |                   |
| Dimmable                                 | DALI              |

| Control interface                   | DALI                       |
|-------------------------------------|----------------------------|
| Mechanical and Housing              |                            |
| Housing Material                    | Aluminum Alloy             |
| Optical cover material              | Polymethyl methacrylate    |
| Housing Color                       | Grey                       |
| Optical cover finish                | Opal                       |
| Ingress protection code             | IP20 [Finger-protected]    |
| Mech. impact protection code        | IK04 [0.5 J standard plus] |
| Optical cover type                  | PMMA                       |
| Net Weight (Piece)                  | 0.310 kg                   |
| Approval and Application            |                            |
| CE mark                             | Yes                        |
| Ambient temperature range           | -20 to +45 °C              |
| Initial Performance (IEC Compliant) |                            |
| Luminous flux tolerance             | -10% / +10%                |
| Power consumption tolerance         | +/-10%                     |

# Greenspace Flex

## Product Data

|                    |                             |
|--------------------|-----------------------------|
| Order product name | RS378B P15 940 PSD-E WB M55 |
| Full product name  | RS378B P15 940 PSD-E WB M55 |
| Full product code  | 911401537571                |
| Order code         | 911401537571                |

|                                 |              |
|---------------------------------|--------------|
| Material Nr. (12NC)             | 911401537571 |
| Numerator - Quantity Per Pack   | 1            |
| Numerator - Packs per outer box | 36           |

## Dimensional drawing

