



Greenspace Flex

RS378B P33 940 PSD-E NB M87

Greenspace Flex, 33 W, 940 neutral white, DALI, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

| General Information | |
|--|-------------------|
| Light source engine type | LED |
| Light Technical | |
| Luminous Flux | 2,400 lm |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 73 lm/W |
| Color rendering index (CRI) | >90 |
| Light source color | 940 neutral white |
| Operating and Electrical | |
| Input Voltage | 220-240 V |
| Line Frequency | 50 or 60 Hz |
| Power Consumption | 33 W |
| Power Factor (Fraction) | 0.9 |
| Number of products on MCB of 16 A type B | - |
| Protection class IEC | Safety class II |
| Controls and Dimming | |
| Dimmable | DALI |

| Control interface | DALI |
|-------------------------------------|----------------------------|
| Mechanical and Housing | |
| Housing Material | Aluminum Alloy |
| Optical cover material | Polymethyl methacrylate |
| Housing Color | Grey |
| Optical cover finish | Opal |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK04 [0.5 J standard plus] |
| Optical cover type | PMMA |
| Net Weight (Piece) | 0.850 kg |
| Approval and Application | |
| CE mark | Yes |
| Ambient temperature range | -20 to +45 °C |
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | -10% / +10% |
| Power consumption tolerance | +/-10% |

Greenspace Flex

Product Data

| | |
|--------------------|-----------------------------|
| Order product name | RS378B P33 940 PSD-E NB M87 |
| Full product name | RS378B P33 940 PSD-E NB M87 |
| Full product code | 911401539171 |
| Order code | 911401539171 |

| | |
|---------------------------------|--------------|
| Material Nr. (12NC) | 911401539171 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |

Dimensional drawing

