



# **Greenspace Flex**

### RS378B P6 927 PSU-E MB M43

Greenspace Flex, 6 W, 927 warm white, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

#### **Product data**

General Information	
Light source engine type	LED
Light Technical	
Luminous Flux	2,540 lm
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	77 lm/W
Color rendering index (CRI)	>90
Light source color	927 warm white
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	6 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	-
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No

Control interface	-
Mechanical and Housing	
Housing Material	Aluminum Alloy
Optical cover material	Polymethyl methacrylate
Housing Color	Grey
Optical cover finish	Opal
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Optical cover type	PMMA
Net Weight (Piece)	0.140 kg
Approval and Application	
CE mark	Yes
Ambient temperature range	-20 to +45 ℃
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Datasheet, 2025, February 2 data subject to change

## **Greenspace Flex**

Product Data	
Order product name	RS378B P6 927 PSU-E MB M43
Full product name	RS378B P6 927 PSU-E MB M43
Full product code	911401532371
Order code	911401532371

Material Nr. (12NC)	911401532371
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48

#### Dimensional drawing





