



# Greenspace Flex

## RS378B P6 930 PSR-E MB M43

Greenspace Flex, 6 W, 930 warm white, Phase-cut dim, IP20 | Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information		Control interface	
Light source engine type	LED		Phase-cut dim
Light Technical		Mechanical and Housing	
Luminous Flux	348 lm	Housing Material	Aluminum Alloy
Correlated Color Temperature (Nom)	3000 K	Optical cover material	Polymethyl methacrylate
Luminous Efficacy (rated) (Nom)	58 lm/W	Housing Color	Grey
Color rendering index (CRI)	>90	Optical cover finish	Opal
Light source color	930 warm white	Ingress protection code	IP20 [Finger-protected]
Operating and Electrical		Mech. impact protection code	IK04 [0.5 J standard plus]
Input Voltage	220-240 V	Optical cover type	PMMA
Line Frequency	50 or 60 Hz	Net Weight (Piece)	0.150 kg
Power Consumption	6 W	Approval and Application	
Power Factor (Fraction)	0.9	CE mark	Yes
Number of products on MCB of 16 A type B	-	Ambient temperature range	-20 to +45 °C
Protection class IEC	Safety class II	Initial Performance (IEC Compliant)	
Controls and Dimming		Luminous flux tolerance	-10% / +10%
Dimmable	TRIAC	Power consumption tolerance	+/-10%

## Greenspace Flex

Product Data	
Order product name	RS378B P6 930 PSR-E MB M43
Full product name	RS378B P6 930 PSR-E MB M43
Full product code	911401533571
Order code	911401533571

Material Nr. (12NC)	911401533571
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48

### Dimensional drawing

