



# GreenUp Linear

## SM308C P22/840 L75W3 PSU MB WH

GreenUp Linear, 22 W, 2150 lm, 4000 K, Frosted, IP20 | Finger-protected

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Linear is the entry level linear product family, which offers the basic functional lighting performance, with multiple choices of installations, lumen outputs and product dimensions.

### Product data

General Information		Controls and Dimming	
Light source engine type	LED	Dimmable	No
		Control interface	-
Light Technical		Mechanical and Housing	
Luminous Flux	2,150 lm	Housing Material	Aluminum extruded
Correlated Color Temperature (Nom)	4000 K	Optical cover material	Polycarbonate
Luminous Efficacy (rated) (Nom)	98 lm/W	Housing Color	White RAL 9003
Color rendering index (CRI)	>80	Optical cover finish	Frosted
Light source color	840 neutral white	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	IK03 [0.3 J]
Operating and Electrical		Optical cover type	Polycarbonate Diffuser
Input Voltage	220-240 V	Net Weight (Piece)	0.830 kg
Line Frequency	50 or 60 Hz		
Power Consumption	22 W	Approval and Application	
Power Factor (Fraction)	0.9	CE mark	No
Number of products on MCB of 16 A type B	95	Ambient temperature range	+20 to +40 °C
Protection class IEC	Safety class II		

## GreenUp Linear

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

### Product Data

Order product name	SM308C P22/840 L75W3 PSU MB WH
Full product name	SM308C P22/840 L75W3 PSU MB WH
Full product code	872016952524599

Order code	911401584222
Material Nr. (12NC)	911401584222
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169525245
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169536739

## Dimensional drawing

