



GreenUp Linear

SP308P P38/865 L140W3 PSU WB WH

GreenUp Linear, 98 lm/W, 865 cool daylight

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Linear is the entry level linear product family, which offers the basic functional lighting performance, with multiple choices of installations, lumen outputs and product dimensions.

Product data

General Information	
Light source engine type	LED
Light Technical	
Luminous Flux	3,750 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	98 lm/W
Color rendering index (CRI)	>80
Light source color	865 cool daylight
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	38 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	55
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No

Control interface	-
Mechanical and Housing	
Housing Material	Aluminum extruded
Optical cover material	Polycarbonate
Housing Color	White RAL 9003
Optical cover finish	Frosted
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Optical cover type	Polycarbonate Diffuser
Net Weight (Piece)	1.430 kg
Approval and Application	
CE mark	No
Ambient temperature range	+20 to +40 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

GreenUp Linear

Product Data	
Order product name	SP308P P38/865 L140W3 PSU WB WH
Full product name	SP308P P38/865 L140W3 PSU WB WH
Full product code	872016952878999
Order code	911401588122
Material Nr. (12NC)	911401588122

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169528789
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169540279

Dimensional drawing

