



GreenUp Linear Flex

SP309P P30/857 L120W4 PSR 1-10V HD 4

GreenUp Linear Flex, 70 lm/W, 857 daylight, depends on driver (1-10V, DALI...)

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Linear Flex is a comprehensive product family which offers a variety of combinations between decorative and functional lighting units. It supports every of your desires with flexible linear family including suspension and recessed installations.

Product data

General Information		Controls and Dimming	
Light source engine type	LED	Dimmable	Yes
		Control interface	depends on driver (1-10V, DALI...)
Light Technical		Mechanical and Housing	
Luminous Flux	2,100 lm	Housing Material	Aluminum extruded
Correlated Color Temperature (Nom)	5700 K	Optical cover material	Polycarbonate
Luminous Efficacy (rated) (Nom)	70 lm/W	Housing Color	Black
Color rendering index (CRI)	>80	Optical cover finish	Frosted
Light source color	857 daylight	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	IK03 [0.3 J]
Operating and Electrical		Optical cover type	Linear-lens array oval shape
Input Voltage	220-240 V	Net Weight (Piece)	1.660 kg
Line Frequency	50 or 60 Hz		
Power Consumption	30 W	Approval and Application	
Power Factor (Fraction)	0.9	CE mark	No
Number of products on MCB of 16 A type B	70	Ambient temperature range	-20 to +40 °C
Protection class IEC	Safety class I		

GreenUp Linear Flex

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	SP309P P30/857 L120W4 PSR 1-10V HD 4
Full product name	SP309P P30/857 L120W4 PSR 1-10V HD 4
Full product code	872016953051599

Order code	911401500032
Material Nr. (12NC)	911401500032
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169530515
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169542006

Dimensional drawing

