



GreenUp Linear Flex

SP309P P55UD/840 L120W5 PSU HD 2 BK

GreenUp Linear Flex, 90 lm/W, 840 neutral white

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Linear Flex is a comprehensive product family which offers a variety of combinations between decorative and functional lighting units. It supports every of your desires with flexible linear family including suspension and recessed installations.

Product data

General Information		Control interface	
Light source engine type	LED	-	
Light Technical		Mechanical and Housing	
Luminous Flux	4,950 lm	Housing Material	Aluminum extruded
Correlated Color Temperature (Nom)	4000 K	Optical cover material	Polycarbonate
Luminous Efficacy (rated) (Nom)	90 lm/W	Housing Color	Black
Color rendering index (CRI)	>80	Optical cover finish	Frosted
Light source color	840 neutral white	Ingress protection code	IP20 [Finger-protected]
Operating and Electrical		Mech. impact protection code	IK03 [0.3 J]
Input Voltage	220-240 V	Optical cover type	Linear-lens array oval shape
Line Frequency	50 or 60 Hz	Net Weight (Piece)	2.790 kg
Power Consumption	55 W	Approval and Application	
Power Factor (Fraction)	0.9	CE mark	No
Number of products on MCB of 16 A type B	37	Ambient temperature range	-20 to +40 °C
Protection class IEC	Safety class II	Initial Performance (IEC Compliant)	
Controls and Dimming		Luminous flux tolerance	+/-10%
Dimmable	No	Power consumption tolerance	+/-10%

GreenUp Linear Flex

Product Data

Order product name	SP309P P55UD/840 L120W5 PSU HD 2 BK
Full product name	SP309P P55UD/840 L120W5 PSU HD 2 BK
Full product code	872016953046199
Order code	911401590422
Material Nr. (12NC)	911401590422

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169530461
Numerator - Packs per outer box	3
EAN/UPC - Case	8720169541955

Dimensional drawing

