



RoadFlair Gen2

BRP491 LED134/WW 100W 220-240V DM GM

RoadFlair Gen2, 13400 lm, 100 W, 730 warm white, Analog, Safety class I

RoadFlair Gen2 is brand new design road lighting product family, set to meet customers' all-round requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optics for various applications fulfillment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair Gen2 competitive price would help on the acceleration of road lighting LED transformation, to a more sustainable society and smarter city.

Product data

General Information	
Driver included	Yes
Service tag	Yes
Light Technical	
Luminous Flux	13,400 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	133 lm/W
Color rendering index (CRI)	>70
Light source color	730 warm white
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Power Consumption	100 W

Power Factor (Fraction)	0.95
Connection	Screw connection block 3-pole
Cable	-
Protection class IEC	Safety class I
Controls and Dimming	
Dimmable	Yes
Control interface	Analog
Mechanical and Housing	
Housing Material	Aluminium pressure die cast
Optical cover material	Polycarbonate
Housing Color	Aluminum and gray
Overall length	355 mm
Overall width	230 mm

Datasheet, 2025, May 8 data subject to change

RoadFlair Gen2

Overall height	136 mm	
Dimensions (Height x Width x Depth)	136 x 230 x 355 mm	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Optical cover type	Polycarbonate micro lens optic	
Net Weight (Piece)	3.600 kg	
Approval and Application		
CE mark	Yes	
Ambient temperature range	-40 to +50 °C	
Initial Performance (IEC Compliant)		


+/-10%

Product Data	
Order product name	BRP491 LED134/WW 100W 220-240V DM GM
Full product name	BRP491 LED134/WW 100W 220-240V DM GM
Full product code	872016972825700
Order code	911401674606
Material Nr. (12NC)	911401674606
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169728257
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169728257

Dimensional drawing

Power consumption tolerance

Luminous flux tolerance





© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.