



RoadFlair Gen2

BRP492 LED201/WW 150W 220-240V DM GM

RoadFlair Gen2, 20100 lm, 150 W, 730 warm white, Analog, Safety class I

RoadFlair Gen2 is brand new design road lighting product family, set to meet customers' all-round requirements, including high lumen efficacy for energy saving and sustainability, aesthetic design for nice shape and appearance, quality material and components for product reliability and long lifetime, professional optics for various applications fulfillment, dimming and system control interface for improving municipal operations and offering future-proof features. RoadFlair Gen2 competitive price would help on the acceleration of road lighting LED transformation, to a more sustainable society and smarter city.

Product data

General Information		Power Factor (Fraction)	0.95
Driver included	Yes	Connection	Screw connection block 3-pole
Service tag	Yes	Cable	-
Light Technical		Protection class IEC	Safety class I
Luminous Flux	20,100 lm	Controls and Dimming	
Correlated Color Temperature (Nom)	3000 K	Dimmable	Yes
Luminous Efficacy (rated) (Nom)	133 lm/W	Control interface	Analog
Color rendering index (CRI)	>70	Mechanical and Housing	
Light source color	730 warm white	Housing Material	Aluminium pressure die cast
Operating and Electrical		Optical cover material	Polycarbonate
Input Voltage	220 to 240 V	Housing Color	Aluminum and gray
Line Frequency	50 or 60 Hz	Overall length	404 mm
Power Consumption	150 W	Overall width	230 mm

RoadFlair Gen2

Overall height	136 mm
Dimensions (Height x Width x Depth)	136 x 230 x 404 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Polycarbonate micro lens optic
Net Weight (Piece)	4.100 kg

Approval and Application

CE mark	Yes
Ambient temperature range	-40 to +50 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data	
Order product name	BRP492 LED201/WW 150W 220-240V DM GM
Full product name	BRP492 LED201/WW 150W 220-240V DM GM
Full product code	872016972834900
Order code	911401674706
Material Nr. (12NC)	911401674706
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169728349
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169728349

Dimensional drawing

