



Uni Wall Mount Recessed

BWP400 LED WW 220V 12W WB PSU 7012

Uni Wall Mount Recessed, 580 lm, 12 W, 730 warm white, Safety class I

Public areas all seek for the most reliable and professional lighting solutions, e.g., parking areas, entrances, outdoor terrace, and wall in garden. The Philips Uni Wall Mount recessed can be installed easily in accordance with per scenario, delivering the optimized lighting to surroundings. The modern sleek design makes the fixture suitable to be installed either in renovation or new installation scenarios. The Philips Uni Wall Mount recessed help you achieve superb reliability and more. Same as other product range in Philips, the product is designed under a variety of Philips quality standard with a good price/quality ratio. Therefore, Philips Uni Wall Mount recessed offers another affordable, energy – efficient and stable choice in wall Mounting family.

Product data

General Information	
Driver included	Yes
Light source engine type	LED
Warranty period	3 years
Light Technical	
Luminous Flux	580 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	48 lm/W
Color rendering index (CRI)	70

Light source color	730 warm white
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Power Consumption	12 W
Power Factor (Fraction)	0.9
Connection	Connection unit 3-pole
Cable	Cable without plug
Protection class IEC	Safety class I

Datasheet, 2025, August 18 data subject to change

Uni Wall Mount Recessed


Controls and Dimming		
Dimmable	No	
Control interface	-	
Mechanical and Housing		
Housing Material	Aluminum die-cast	
Optical cover material	Tempered glass	
Housing Color	Gray	
Overall length	205 mm	
Overall width	107 mm	
Overall height	71 mm	
Dimensions (Height x Width x Depth)	71 x 107 x 205 mm	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Optical cover type	Flat glass	
Net Weight (Piece)	0.890 kg	
Approval and Application		

Yes

Ambient temperature range	-40 to +50 °C	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-10%	
Power consumption tolerance	+/-10%	
Product Data		
Order product name	BWP400 LED WW 220V 12W WB PSU 7012	
Full product name	BWP400 LED WW 220V 12W WB PSU 7012	
Full product code	692382861102699	
Order code	911401698508	
Material Nr. (12NC)	911401698508	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	6923828611026	
Numerator - Packs per outer box	12	
EAN/UPC - Case	6923828611286	

Dimensional drawing

CE mark





© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.