



Uni Wall Sconce

BWP410 LED WW 220V 40W MB PSU 7012

Uni Wall Sconce, 5000 lm, 40 W, 730 warm white, Safety class I

Public areas all seek for the most reliable and professional lighting solutions, e.g., parking areas, entrances, outdoor terrace, and wall in garden. The Philips Uni Wall Mount Sconce can be installed easily in accordance with per scenario, delivering the optimized lighting to surroundings. The modern sleek design makes the fixture suitable to be installed either in renovation or new installation scenarios. The Philips Uni Wall Mount sconce helps you achieve superb reliability and more. Same as other product range in Philips, the product is designed under a variety of Philips quality standard with a good price/quality ratio. Therefore, Philips Uni Wall Mount Sconce offers another affordable, energy – efficient and stable choice in the existing wall Mounting family.

Product data

General Information		Power Consumption	
Driver included	Yes	40 W	
Light source engine type	LED	Power Factor (Fraction)	
Warranty period	3 years	0.95	
Light Technical		Connection	
Luminous Flux	5,000 lm	Connection unit 3-pole	
Correlated Color Temperature (Nom)	3000 K	Cable	
Luminous Efficacy (rated) (Nom)	125 lm/W	Cable without plug	
Color rendering index (CRI)	70	Protection class IEC	
Light source color	730 warm white	Safety class I	
Operating and Electrical		Controls and Dimming	
Input Voltage	220 to 240 V	Dimmable	
Line Frequency	50 or 60 Hz	No	
		Control interface	
		-	
		Mechanical and Housing	
		Housing Material	
		Aluminum die-cast	
		Optical cover material	
		Tempered glass	
		Housing Color	
		Gray	
		Overall length	
		222 mm	

Uni Wall Sconce

Overall width	150 mm
Overall height	359 mm
Dimensions (Height x Width x Depth)	359 x 150 x 222 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Flat glass
Net Weight (Piece)	4.190 kg

Approval and Application

CE mark	Yes
Ambient temperature range	-40 to +50 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
-------------------------	--------

Power consumption tolerance	+/-10%
-----------------------------	--------

Product Data

Order product name	BWP410 LED WW 220V 40W MB PSU 7012
Full product name	BWP410 LED WW 220V 40W MB PSU 7012
Full product code	692382861083899
Order code	911401696808
Material Nr. (12NC)	911401696808
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828610838
Numerator - Packs per outer box	4
EAN/UPC - Case	6923828611095

Dimensional drawing

